



chemical solutions to concrete problems

PRE-FORM 100

100% SOLIDS EPOXY PLYWOOD FORM COATING



Extend
Form Life
and Deliver
a Flawless
Finish

ACHIEVE
MORE
POURS



SELF
LEVELING



40 MINUTE
WORKING
TIME



EASY
APPLICATION



BENEFITS

- **100% Solids:** High-build, solvent-free, self-leveling, epoxy coating for sealing architectural plywood forms
- **Smooth, Uniform Finish:** Transforms rough, non-overlaid plywood and dimensional wood forms into smooth architectural quality forms
- **Seals Plywood Forms:** eliminates wood grain transfer and sugar-related concrete surface discoloration and staining in architectural concrete applications
- **Self-Leveling:** Easy-to-apply with either a notched squeegee or spiked roller
- **Safer for Workers:** Safe for interior application and is nearly odor-free
- **Working Time:** 40-minute working time on form surface
- Convenient 2:1 mix ratio



nox-crete.com • 402-341-2080

FOLLOW US





CONSISTENT UNIFORM FINISH



HIGH-BUILD FORMULA



ARCHITECTURAL DETAIL DELIVERED

Pre-Form 100 is a two-component epoxy plywood form coating that seals and protects form surfaces, creating an impact-resistant, glossy, seamless, smooth and long-lasting casting surface. The high-build, solvent-free, self-leveling epoxy coating eliminates all concrete surface voids and other surface irregularities.

APPLICATIONS

- Two versions available; Pre-Form 100 and Pre-Form 100 Fast Cure - used when temperatures are below 60° F
- Product is transparent, red pigment packs are optional to help see exactly where product has been applied
- The typical application rate on standard horizontal plywood forms is 50-100 sf / gal (1.25 -2.5 sm / L) or 16-32 mil, the standard practice in precast plants is to apply two coats
- PRE-FORM 100 is easily applied with a notched squeegee and roller applicator equipped with a 3/8 inch nap cover. Spiked rollers should be used after application to help remove entrapped air and ensure a smooth finish
- Application equipment can be purchased from Nox-Crete

PACKAGING

- 4 gallon (15.1 L) kit
- 15 gallon (57 L) kit
- 165 gallon (624 L) kit



SCAN FOR INFO

nox-crete.com • 402-341-2080

FOLLOW US

