

NOX-CRETE PACFORM

Wall panel edgeform for precast and tilt-up.

HOW IT WORKS

NOX-CRETE PACFORM is a precision engineered non-structural laminated veneer lumber (LVL) edgeform that is factory sealed with a high solids, baked on, protective acrylic coating to eliminate edge swelling and to prevent wood sugar migration. Our LVL edgeforms save time, reduce waste, lower costs and remain uniformly flat and true after multiple pours.

APPLICATIONS

- ◆ To be used as a wall panel edgeform for precast and tilt-up construction.

ADVANTAGES

- ◆ Straight and true – will not warp, even after multiple uses.
- ◆ Available in custom widths up to 13.25 in (33.7 cm) and special order widths up to 48 in (122 cm).
- ◆ Eliminates the need for stacking smaller width forms.
- ◆ 16 ft (4.9 m) lengths allows for fast alignment with less splicing.
- ◆ Stronger – requires up to 40% less bracing compared to ¾ inch plywood and some types of dimensional lumber.
- ◆ 10 reuses are typical and up to 20 reuses are possible.
- ◆ Substantially outlasts dimensional lumber, traditional laminated veneer lumber (LVL) and laminated strand lumber (LSL).
- ◆ Reduces material costs and jobsite waste.
- ◆ Face and back are comprised of “C” grade veneer with no splits and no open knots.
- ◆ Lighter weight compared to green (wet) dimensional lumber and laminated strand lumber (LSL).
- ◆ Eliminates the need for sorting and culling.
- ◆ Designed specifically for tilt-up and precast wall panel production.
- ◆ Compatible with Nox-Crete’s CLEAN LINE REVEAL extruded PVC chamfer products and SILCOSEAL water-based bondbreakers.

⚠ PRECAUTIONS ⚠

- ◆ For best results, we recommend Nox-Crete chemically active water-based form release agents and bondbreakers.
- ◆ Not recommended for use with solvent-based bondbreakers or form release agents.

STRIPPING

- ◆ Proper form stripping and handling procedures will prolong the life of the product. Wood wedges are recommended for stripping panels rather than metal tools. Protect form edges from unnecessary abrasion.

FORM CLEANING

- ◆ Soon after removal, forms should be inspected for wear, cleaned, repaired, and retreated with a water-based, Nox-Crete chemically reactive release agent or bondbreaker prior to reuse. A hardwood wedge is preferred over wire brushes when cleaning forms.

TECHNICAL DATA

Thickness	1.25 in (317 mm)
Length	16 ft (4.9 m)
Widths	2½ in to 13¼ in (5.7 cm to 33.7 cm)
Custom Sizes	Please Inquire

PACKAGING

PACFORM comes in bundles that vary in quantity depending upon the width. Protective weatherproof covers are available.

HANDLING/STORAGE

For maximum life, PACFORM should be stored out of the sun and rain or covered loosely to allow circulation without heat and/or moisture build up. Use wood or plastic stickers thick enough to keep products away from ground moisture, including snow. Keep PAC FORM away from areas of standing water and heavy traffic.

AVAILABILITY & TECHNICAL SERVICES

In addition to corporate offices in Omaha, Nebraska, Nox-Crete Products Group maintains regional offices and distribution centers in principal markets throughout the world. For source or technical information, call 800-669-2738 or 402-341-2080.

LIMITED WARRANTY

NOTICE-READ CAREFULLY

CONDITIONS OF SALE

NOX-CRETE warrants this product for sale subject to, and Buyer and all users are deemed to have accepted, the following conditions of sale and limited warranty which may only be varied by written agreement of a duly authorized corporate officer of NOX-CRETE. No other representative of or for NOX-CRETE is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

NOX-CRETE warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, NOX-CRETE will replace the defective product with new product without charge to the purchaser.

NOX-CRETE makes NO OTHER WARRANTY, either express or implied, concerning this product. There is NO WARRANTY OF MERCHANTABILITY. In no case shall NOX-CRETE be liable for special, indirect or consequential damages resulting from the use or handling of the product and no claim of any kind shall be greater in amount than the purchase price of the product in respect of which damages are claimed.

INHERENT RISKS

NOX-CRETE MAKES NO WARRANTY WITH RESPECT TO THE PERFORMANCE OF THE PRODUCT AFTER IT IS APPLIED BY THE PURCHASER, AND PURCHASER ASSUMES ALL RISKS ASSOCIATED WITH THE USE OR APPLICATION OF THE PRODUCT.



chemical solutions to concrete problems

Updated 05/02/18. This version supersedes all previous versions.