



chemical solutions to concrete problems

NOX-CARB DARK BASE 350 COMPONENT A

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Form	Mixture
Trade Name	NOX-CARB DARK BASE 350 COMPONENT A
Product Code	NCDB350A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use Industrial. For professional use only.

1.2.2 Uses Advised Against

No additional information available

1.3 Details of the supplier of the safety data sheet

Manufacturer

NOX-CRETE, INC.
1444 SOUTH 20TH STREET
OMAHA, NE 68108
Tel: 402-341-2080
Fax: 402-341-9752
E-Mail: corporate@nox-crete.com
Web Site: www.nox-crete.com

1.4 Emergency telephone number

Emergency Number	Chemtrec (800) 424-9300 Chemtrec Outside of U.S. 703-527-3887
------------------	--

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulations 29CFR 1910.1200 , (EC) No. 1272/2008(CLP)(GHS)

Flam Liq. 2	H225
Skin Irr. 2	H315
Eye Dam. 1	H318
Acute Tox. 4 (inhalation)	H332
STOT SE 3 resp. irrit.	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351

Full text of H phrases see section 16

Adverse physiochemical, human health and environmental effects

No additional information available

2.2 Label elements

Hazard pictograms



Signal word

Danger



chemical solutions to concrete problems

NOX-CARB DARK BASE 350 COMPONENT A

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

Hazard statements

H225 - Highly flammable liquid and vapor
H304 – May be fatal if swallowed and enters airways
H315 – Causes skin irritation
H318 – Causes serious eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer

Precautionary statements

Prevention:

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/light/equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 – Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash all exposed external body areas thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response:

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower
P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice/attention
P310 - Immediately call POISON CENTER/ doctor/ physician/ first aider if you feel unwell.
P331 - Do NOT induce vomiting
P332+P313 – if skin irritation occurs: Get medical advice/attention.
P362+P364 – Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction
P403+P405+P235+P233 - Store locked up in a cool well-ventilated place. Keep container tightly closed.
P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

Storage:

Disposal:

2.3 Other hazards

Full text of H and P phrases: see section 16

Section 3. Composition / information on ingredients

3.1 Substances



chemical solutions to concrete problems

NOX-CARB DARK BASE 350 COMPONENT A

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

Not applicable

3.2 Mixture

Classification according to Regulations 29CFR 1910.1200 , (EC) No. 1272/2008(CLP)(GHS)

Name	Product identifier	%
Exempt Solvent	Trade Secret	Trade Secret
Solvent Naphtha	Trade Secret	Trade Secret
Xylene	1330-20-7	< 0.4
1,2,4- Trimethylbenzene	95-63-6	< 2.0
Cumene	98-82-8	< 0.3
Ethylbenzene	100-41-4	< 0.1
1,3,5-Trimethylbenze	108-67-8	< 2.0
1,2,3-Trimethylbenzene	526-73-8	< 2.0

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration may be withheld as Trade Secret, while all health and safety properties and effects are included in the SDS. Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).

Section 4. First aid measures

4.1 Description of first aid measures

First-aid measures general

Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person.

First-aid measures after inhalation

If the individual experiences nausea, dizziness, has difficulty in breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a Poison Center or doctor/physician.

First-aid measures after skin contact

If skin irritation persists, seek medical attention. Remove or take off immediately all contaminated clothing. Rinse skin with water or shower. Wash off immediately with soap and plenty of water.

First-aid measure after eye contact

When contact lenses are worn, remove if possible. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.

First-aid measures after ingestion

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately.

4.2 Most important symptoms and effects, acute and delayed

Symptoms/injuries after inhalation

May cause irritation to the respiratory tract. Overexposure to vapors may result in headache, nausea, drowsiness or dizziness.

Symptoms/injuries after skin contact

May cause skin irritation or burning sensation

Symptoms/injuries after eye contact

May cause eye irritation or injury

Symptoms/injuries after ingestion

May cause severe irritation or burns to the mucous membrane of the mouth, throat, esophagus and stomach

4.3 Indication of any immediate medical attention and special treatment needed

No additional information available



chemical solutions to concrete problems

NOX-CARB DARK BASE 350 COMPONENT A

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Section 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry chemical, foam, carbon dioxide

Unsuitable extinguishing media

Do not use heavy water stream

5.2 Special hazards arising from the substance or mixture

Reactivity

Thermal decomposition products may cause a health hazard.

5.3 Advice for firefighters

Firefighting instructions

Flammable Liquid! This material releases vapors when heated above ambient temperatures. Vapors can cause a flash fire. Use water spray or fog to cool exposed containers.

Protective equipment for firefighters

Firefighters should always wear self-contained breathing apparatus (SCBA) and full protective gear when fighting any chemical fire.

Other information

On heating or burning harmful gasses/vapors may be released. This product may cause the floor to become slippery.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General measures

Extremely Flammable. Eliminate any ignition sources. Dike or impound spilled material. Use non-sparking tools. All equipment must be grounded. Take proper precautions to ensure your own health and safety before attempting spill control or cleanup.

6.11 Protective Equipment

Equip cleanup crew with proper protective equipment.

6.2 Environmental precautions

Prevent entry to sewers and public waters.

Notify authorities if liquid enters sewers or public waters.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up

Soak up spills with inert solids, such as clay or diatomaceous earth. Collect into vapor tight containers and dispose of properly.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measures

Wash hands and other exposed areas with soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use keep containers tightly closed. Avoid breathing vapor or mist.

Hygiene measures

Wash contaminated clothing before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Store in accordance with local regulations. Store in original container in a cool well-ventilated place away from heat, sparks and open flame. Keep containers tightly closed until ready for use.

Incompatible materials

Strong oxidizing agents

Storage temperature

Store in a cool dry environment away from sources of ignition.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient name	Occupational exposure limits ACGIH TLV (United States)
Xylene	TWA: 100 ppm 8 hours



chemical solutions to concrete problems

NOX-CARB DARK BASE 350 COMPONENT A

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

Cumene	TWA: 50 ppm 8 hours
1,2,4- Trimethylbenzene	TWA: 25 ppm 8 hours
Solvent Naphtha	TWA: 100 ppm 8 hours
Ethylbenzene	TWA: 100 ppm 8 hours
1,3,5-Trimethylbenzene	TWA: 25 ppm 10 hours
1,2,3-Trimethylbenzene	TWA: 25 ppm 10 hours

8.2 Exposure controls

Appropriate engineering controls

Use with adequate ventilation to keep product vapor concentrations below specified TLV

Eye and face protection

Chemical goggles and/or face shields are recommended to prevent potential eye contact, irritation or injury.

Skin protection

Wear chemical resistant gloves and appropriate protective clothing and boots as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.

Respiratory protection

General room ventilation is normally adequate. Avoid breathing the product mist or vapors. The use of an appropriate respirator is recommended whenever the airborne concentrations exceed the TLV.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Gray liquid
Odor	Strong Aromatic Odor
Odor Threshold	No data available
PH	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	No data available
Flash point	> 18 C > 65 F PMCC
Relative evaporation rate (butyl acetate=1)	No data available
Flammability (solid, gas)	Flammable liquid and vapor
Upper/lower explosive limits	No data available
Vapor pressure	No data available
Vapor density	No data available
Relative density (Specific gravity)	1.291 Kg per Liter 10.774 Lbs per Gallon
Solubility	Water: Negligible
Partition coefficient n-octanol/water	No data available
Auto-ignition temperature	Not applicable
Viscosity	No data available
VOC content	Less than 350 g/l

Section 10. Stability and reactivity

10.1 Reactivity

No additional information available

10.2 Chemical stability

Stable under normal conditions

10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4 Conditions to avoid

Extreme high or low temperatures.

10.5 Incompatible materials

Strong acids and oxidizers

10.6 Hazardous decomposition products

carbon monoxide, carbon dioxide, various hydrocarbon derivatives

Section 11. Toxicology information



chemical solutions to concrete problems

NOX-CARB DARK BASE 350 COMPONENT A

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

11.1 Information on toxicological effects

Acute toxicity	No adverse effects expected under intended use.
Irritation/Corrosion	May cause skin irritation
Skin	May cause serious eye irritation and damage.
Eyes	May cause respiratory irritation
Respiration or skin sensitization	No data available
Germ cell mutagenicity	

Carcinogenicity IARC

Xylene	3
Cumene	2B
Ethylbenzene	2B

2B - Limited evidence in humans and less than sufficient evidence in animals.

3 - Inadequate in humans and inadequate or limited in animals.

Reproductive toxicity	No data available
Specific target organ toxicity	
Single exposure	No data available
Repeated exposure	No data available
Aspiration hazard	May be fatal if swallowed and enters airways

Section 12. Ecological information

12.1 Ecotoxicity	Not established
12.2 Persistence and degradability	Not established
12.3 Bio accumulative potential	Not established
12.4 Mobility in soil	No additional information available
12.5 Other adverse effects	Avoid release to the environment

SECTION 13. Disposal Considerations

13.1 Waste treatment methods	The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
-------------------------------------	--

SECTION 14. Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA	
14.1 UN number	UN1263
14.2 UN proper shipping name	Paint Related Material
14.3 Transport hazard class(es)	3
14.4 Packing group	II
14.5 Environmental hazards	No additional information available
14.6 Special precautions for user	
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No additional information available
14.8 Transport in bulk according to CFR 49 173.15	Not applicable



chemical solutions to concrete problems

NOX-CARB DARK BASE 350 COMPONENT A

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation (HPR)* (WHMIS 2015)

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.2 USA Regulations

Section 313

Contains the following ingredients at or above the reporting level requirements of Section 313. This information must be included in all SDS's copied or distributed for this material.

CHEMICAL	CAS #	MAX WEIGHT %
Xylene	1330-20-7	1.2
1,2,4- Trimethylbenzene	95-63-6	6.0
Cumene	98-82-8	1.2
Ethylbenzene	100-41-4	0.3
1,3,5-Trimethylbenzene	108-67-8	< 2.0
1,2,3-Trimethylbenzene	526-73-8	< 2.0

TSCA

Proposition 65

All ingredients are listed or exempted

WARNING NOT FOR SALE IN CALIFORNIA

15.1.3 Canada Regulations

This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

DSL

15.2 Chemical safety assessment

All ingredients are listed or exempted

A Chemical Safety Assessment has not been carried out.

Section 16. Other information

Date of issue/revision	9-10-2024
Version	3.1
Number	1025
Date of previous issue/revision	1-24-2024
Preparer	Nox-Crete, Inc.
<u>Reference Documentation</u>	

The information and recommendations contained herein are, to the best of Nox-Crete, Inc.'s knowledge and belief, accurate and reliable as of the date issued. You can contact Nox-Crete, Inc. to ensure that this document is the most current available from Nox-Crete, Inc. The information and recommendations are offered for the buyer's/user's consideration and examination. It is the buyer's/user's responsibility to satisfy themselves that the product is suitable for the intended use. Appropriate warnings and safe-handling procedures should be provided to all handlers and users. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Since the information provided herein may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and buyer/user may rely thereon only at their risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further, since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each buyer/user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. If buyer/user repackages this product, it is the buyer's/user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Nox-Crete, Inc. urges each customer or recipient of this SDS to study it carefully and consult appropriate



chemical solutions to concrete problems

NOX-CARB DARK BASE 350 COMPONENT A

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with this product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part is not permitted.

Full text of H and P phrases

Flam Liq. 2	H225
Skin Irr. 2	H315
Eye Dam. 1	H318
Acute Tox. 4 (inhalation)	H332
STOT SE 3 resp. irrit.	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/light/equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash all exposed external body areas thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - IF exposed or concerned: Get medical advice/attention

P310 - Immediately call POISON CENTER/ doctor/ physician/ first aider if you feel unwell.

P331 - Do NOT induce vomiting

P332+P313 - if skin irritation occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse

P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction

P403+P405+P235+P233 - Store locked up in a cool well-ventilated place. Keep cool.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.