

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Form Mixture

Trade Name NOX-CARB DARK BASE COMPONENT A

Product Code NCSPDBA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Jse Industrial. For professional use only.

1.2.2 Uses Advised Against

No additional information available

1.3 Details of the supplier of the safety data sheet

Manufacturer

NOX-CRETE, INC.

1444 SOUTH 20TH STREET

OMAHA, NE 68108 Tel: 402-341-2080 Fax: 402-341-9752

E-Mail: corporate@nox-crete.com
Web Site: www.nox-crete.com

1.4 Emergency telephone number

Emergency Number Chemtrec (800) 424-9300

Chemtrec Outside of U.S. 703-527-3887

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulations 29CFR 1910.1200, (EC) No. 1272/2008(CLP)(GHS)

Flam Liq. 3 H226
Asp. Tox. 1 H304
resp. irrit. STOT SE 3 H335
STOT SE 3 drowsiness H336
Carc. 2 H351

Full text of H phrases see section 16

Adverse physiochemical, human health and environmental effects

No additional information available

2.2 Label elements

Hazard pictograms







Signal word Hazard statements

Danger

H226 - Flammable liquid and vapor

vavs

Flam Liq. 3

H304 - May be fatal if swallowed and enters airways

EN (English) Page 1 of 8



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H351 - Suspected of causing cancer

Precautionary statements

Prevention: P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and

understood

P210 - Keep away from heat/sparks/open flames/hot surfaces-No

smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/light/equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face

protection

Response: P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or

doctor/physician

P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off

immediately all contaminated clothing. Rinse skin with water / shower P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest

in a position comfortable for breathing.

P308+P313 - IF exposed or concerned: Get medical advice/attention

P331 - Do NOT induce vomiting

P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for

extinction

Storage: P403+P405+P235+P233 - Store locked up in a cool well-ventilated

place. Keep container tightly closed.

Disposal: P501 - Dispose of contents/container in accordance with

local/regional/national/international regulations.

2.3 Other hazards

Full text of H and P phrases: see section 16

Section 3. Composition / information on ingredients

3.1 Substances

Not applicable

3.2 Mixture

Classification according to Regulations 29CFR 1910.1200, (EC) No. 1272/2008(CLP)(GHS)

Name	Product identifier	%
Xylene	1330-20-7	< 1.2
Solvent Naphtha	Trade Secret	Trade Secret
1,2,4- Trimethylbenzene	95-63-6	< 18

EN (English) Page 2 of 8



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Cumene	98-82-8	< 0.6

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration may be withheld as Trade Secret, while all health and safety properties and effects are included in the SDS. Balance of other ingredients are nonhazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).

Section 4. First aid measures

Description of first aid measures

First-aid measures general Get medical advice/attention if you feel unwell. Never give anything by

mouth to an unconscious person.

If the individual experiences nausea, dizziness, has difficulty in First-aid measures after inhalation

> breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a Poison Center or doctor/physician.

First-aid measures after skin contact If skin irritation persists, seek medical attention. Remove or take off

immediately all contaminated clothing. Rinse skin with water or shower.

Wash off immediately with soap and plenty of water.

When contact lenses are worn, remove if possible. In case of contact First-aid measure after eye contact

with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.

First-aid measures after ingestion Rinse mouth. DO NOT induce vomiting. Get medical attention

immediately.

Most important symptoms and effects, acute and delayed

Symptoms/injuries after inhalation May cause irritation to the respiratory tract. Overexposure to vapors may

result in headache, nausea, drowsiness or dizziness.

May cause skin irritation or burning sensation

Symptoms/injuries after skin contact

Symptoms/injuries after eye contact May cause eye irritation or injury

Symptoms/injuries after ingestion May cause severe irritation or burns to the mucous membrane of the

mouth, throat, esophagus and stomach

4.3 Indication of any immediate medical attention and special treatment needed

No additional information available

Section 5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Dry chemical, foam, carbon dioxide Unsuitable extinguishing media Do not use heavy water stream

Special hazards arising from the substance or mixture

Reactivity Thermal decomposition products may cause a health hazard.

5.3 Advice for firefighters

Firefighting instructions Flammable Liquid! This material releases vapors when heated above

ambient temperatures. Vapors can cause a flash fire. Use water spray

or fog to cool exposed containers.

Firefighters should always wear self-contained breathing apparatus Protective equipment for firefighters

(SCBA) and full protective gear when fighting any chemical fire.

On heating or burning harmful gasses/vapors may be released. Other information

This product may cause the floor to become slippery.

Section 6. Accidental release measures

EN (English) Page 3 of 8



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

6.1 Personal precautions, protective equipment and emergency procedures

General measures Extremely Flammable. Eliminate any ignition sources. Dike or impound

spilled material. Use Non-sparking tools. All equipment must be grounded. Take proper precautions to ensure your own health and

safety before attempting spill control or cleanup.

<u>6.11 Protective Equipment</u> Equip cleanup crew with proper protective equipment.

6.2 Environmental precautions Prevent entry to sewers and public waters.

Notify authorities if liquid enters sewers or public waters.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning upSoak up spills with inert solids, such as clay or diatomaceous earth.

Collect into vapor tight containers and dispose of properly.

Section 7. Handling and storage

7.1 Precautions for safe handling

Protective measuresWash hands and other exposed areas with soap and water before

eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use

keep containers tightly closed. Avoid breathing vapor or mist.

Hygiene measures Wash contaminated clothing before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditionsStore in accordance with local regulations. Store in original container in

a cool well-ventilated place away from heat, sparks and open flame.

Keep containers tightly closed until ready for use.

Incompatible materialsStrong oxidizing agents

Storage temperature Store in a cool dry environment away from sources of ignition.

Section 8. Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient name	Occupational exposure limits ACGIH TLV (United States)
Xylene	TWA: 100 ppm 8 hours
Cumene	TWA: 50 ppm 8 hours
1,2,4- Trimethylbenzene	TWA: 25 ppm 8 hours
Solvent Naphtha	TWA: 100 ppm 8 hours

8.2 Exposure controls

Appropriate engineering controls

Use with adequate ventilation to keep product vapor concentrations

below specified TLV

Eye and face protectionChemical goggles and/or face shields are recommended to prevent

potential eye contact, irritation or injury.

Skin protection Wear chemical resistant gloves and appropriate protective clothing and

boots as required to prevent skin contact. Wash exposed skin

frequently with soap and water. Soiled clothing should be laundered

before reuse.

Respiratory protectionGeneral room ventilation is normally adequate. Avoid breathing the

product mist or vapors. The use of an appropriate respirator is

recommended whenever the airborne concentrations exceed the TLV.

Section 9. Physical and chemical properties

EN (English) Page 4 of 8



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

9.1 Information on basic physical and chemical properties

Appearance Grav liquid

Odor Strong Aromatic Odor
Odor Threshold No data available
PH No data available
Melting point No data available
Freezing point No data available
Boiling point > 138 C (>280 F)

Flash point > 38 C > 100 F PMCC

Relative evaporation rate (butyl acetate=1) No data available

Flammability (solid, gas) Flammable liquid and vapor

Upper/lower explosive limitsNo data availableVapor pressureNo data availableVapor densityNo data available

Relative density (Specific gravity) 1.28 Kg per Liter 9.4 Lbs per Gallon

Solubility Water: Negligible
Partition coefficient n-octanol/water No data available
Auto-ignition temperature Not applicable
Viscosity No data available
VOC content Less than 600 g/l

Section 10. Stability and reactivity

10.1ReactivityNo additional information available10.2Chemical stabilityStable under normal conditions

10.3 Possibility of hazardous reactions
 10.4 Conditions to avoid
 Hazardous polymerization will not occur.
 Extreme high or low temperatures.

10.5 Incompatible materials Strong acids and oxidizers

10.6 Hazardous decomposition products carbon monoxide, carbon dioxide, various hydrocarbon derivatives

Section 11. Toxicology information

11.1 Information on toxicological effects

Acute toxicity No adverse effects expected under intended use.

Irritation/Corrosion Skin May cause skin irritation

Eyes May causes serious eye irritation and damage.

Respiration or skin sensitization May cause respiratory irritation

Germ cell mutagenicity No data available

Carcinogenicity IARC

Xylene	3
Cumene	2B

2B - Limited evidence in humans and less than sufficient evidence in animals.

3 - Inadequate in humans and inadequate or limited in animals.

Reproductive toxicity

No data available

Specific target organ toxicity

Single exposure

No data available
Repeated exposure

No data available

Aspiration hazard May be fatal if swallowed and enters airways

EN (English) Page 5 of 8



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Section 12. Ecological information

12.1 EcotoxicityNot established12.2 Persistence and degradabilityNot established12.3 Bio accumulative potentialNot established

12.4 Mobility in soilNo additional information available12.5 Other adverse effectsAvoid release to the environment

SECTION 13. Disposal Considerations

13.1 Waste treatment methodsThe user of this material has the responsibility to dispose of unused

material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

SECTION 14. Transport information

In accordance with US DOT Not dangerous goods in sense of transport regulations.

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1 UN number UN1263

14.2 UN proper shipping name Paint Related Material

14.3 Transport hazard class(es) 3 14.4 Packing group III

14.5 Environmental hazards No additional information available

14.6 Special precautions for user 14.7 Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code No additional information available

14.8 Transport in bulk according to

CFR 49 173.15 Not applicable

SECTION 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.2 USA Regulations

Section 313 Contains the following ingredients at or above the reporting level

requirements of Section 313. This information must be included in all

SDS's copied or distributed for this material.

CHEMICAL CAS # MAX WEIGHT %

 Xylene
 1330-20-7
 1.2

 1,2,4- Trimethylbenzene
 95-63-6
 18.0

 Cumene
 98-82-8
 0.6

TSCA All ingredients are listed or exempted

Proposition 65 WARNING NOT FOR SALE IN CALIFORNIA

15.1.3 Canada Regulations This SDS has been prepared according to the hazard criteria of the

Controlled Products Regulations (CPR) and the SDS contains all of the

information required by the CPR.

DSL All ingredients are listed or exempted

15.2 Chemical safety assessment A Chemical Safety Assessment has not been carried out.

Section 16. Other information



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Date of issue 7-17-2023

Version 3.0
Number 115
Date of previous issue 8-5-2021
Preparer Nox-Crete, Inc.

Reference Documentation

The information and recommendations contained herein are, to the best of Nox-Crete, Inc.'s knowledge and belief, accurate and reliable as of the date issued. You can contact Nox-Crete, Inc. to ensure that this document is the most current available from Nox-Crete, Inc. The information and recommendations are offered for the buyer's/user's consideration and examination. It is the buyer's/user's responsibility to satisfy themselves that the product is suitable for the intended use. Appropriate warnings and safe-handling procedures should be provided to all handlers and users. Since conditions for use of the product are not under the control of the manufacturer, it is the buver's/user's duty to determine the conditions necessary for the safe use of this product. Since the information provided herein may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and buyer/user may rely thereon only at their risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further, since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each buyer/user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. If buyer/user repackages this product, it is the buyer's/user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Nox-Crete, Inc. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with this product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part is not permitted.

Full text of H and P phrases

Flam Liq. 3	H226
Asp. Tox. 1	H304
resp. irrit. STOT SE 3	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351

H226 - Flammable liquid and vapor Flam Liq. 3

H304 - May be fatal if swallowed and enters airways

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/light/equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

EN (English) Page 7 of 8



Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313 - IF exposed or concerned: Get medical advice/attention

P331 - Do NOT induce vomiting

P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction

P403+P405+P235+P233 - Store locked up in a cool well-ventilated place. Keep container tightly closed.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.

EN (English) Page 8 of 8