

NOX-CARB LIGHT BASE COMPONENT A Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Section 1. Identification of the substance/mixture and of the company/undertaking

 1.1
 Product identifier

 Product Form
 Mixture

 Trade Name
 NOX-CARB LIGHT BASE COMPONENT A

 Product Code
 NCSPLBA

 1.2
 Relevant identified uses of the substance or mixture and uses advised against

 Use
 Industrial. For professional use only.

 1.2.2 Uses Advised Against
 No additional information available

 1.3
 Details of the supplier of the safety data sheet

 Manufacturer
 Manufacturer

NOX-CRETE, INC. 1444 SOUTH 20TH STREET OMAHA, NE 68108 Tel: 402-341-2080 Fax: 402-341-9752 E-Mail: <u>corporate@nox-crete.com</u> Web Site: <u>www.nox-crete.com</u>

1.4 Emergency telephone number

Emergency Number

Chemtrec (800) 424-9300 Chemtrec Outside of U.S. 703-527-3887

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Flam Liq. 3	H226
Asp. Tox. 1	H304
resp. irrit. STOT SE 3	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351

Full text of H phrases see section 16Adverse physiochemical, human health and environmental effectsNo additional information available2.2 Label elementsHazard pictograms



Signal word Hazard statements Danger H226 - Flammable liquid and vapor H304 - May be fatal if swallowed and enters airways

Flam Liq. 3

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness



NOX-CARB LIGHT BASE COMPONENT A Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

	H351 - Suspected of causing cancer
Precautionary statements	
Prevention:	P201 - Obtain special instructions before use
	P210 - Keep away from heat/sparks/open flames/hot surfaces-No smoking
	P240 - Ground/bond container and receiving equipment
	P241 - Use explosion-proof electrical/ventilating/light/equipment P242 - Use only non-sparking tools
	P243 - Take precautionary measures against static discharge
	P261 Avoid breathing dust/fume/gas/mist/vapors/spray
	P271 - Use only outdoors or in a well-ventilated area
	P280 - Wear protective gloves/protective clothing/eye protection/face protection
Response:	P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
	P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off
	immediately all contaminated clothing. Rinse skin with water / shower
	P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P312 Call a poison center/doctor if you feel unwell.
	P331 - Do NOT induce vomiting
	P370+P378 - In case of fire: Use Dry chemical, foam, carbon dioxide for extinction
Storage:	P403+P405+P235+P233 - Store locked up in a cool well-ventilated
5	place. Keep container tightly closed.
Disposal:	P501 - Dispose of contents/container in accordance with
-	local/regional/national/international regulations.

2.3 Other hazards

Full text of H and P phrases: see section 16

Section 3. Composition / information on ingredients

3.1 Substances

Not applicable

3.2 Mixture

Name	Product identifier	%
Xylene	1330-20-7	< 1.1
Solvent Naphtha	Trade Secret	Trade Secret
1,2,4- Trimethylbenzene	95-63-6	< 16
Cumene	98-82-8	< 0.5

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration may be withheld as Trade Secret, while all health and safety properties and effects are included in the SDS. Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).



NOX-CARB LIGHT BASE COMPONENT A Safety Data Sheet According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015) NOX-CARB LIGHT BASE COMPONENT A

4.4 Description of first sides sources	
4.1 Description of first aid measures	
First-aid measures general	Get medical advice/attention if you feel unwell. Never give anything by
	mouth to an unconscious person.
First-aid measures after inhalation	If the individual experiences nausea, dizziness, has difficulty in breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a Poison Center or doctor/physician.
First-aid measures after skin contact	If skin irritation persists, seek medical attention. Remove or take off immediately all contaminated clothing. Rinse skin with water or shower. Wash off immediately with soap and plenty of water.
First-aid measure after eye contact	When contact lenses are worn, remove if possible. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.
First-aid measures after ingestion	Rinse mouth. DO NOT induce vomiting. Get medical attention immediately.
4.2 Most important symptoms and effects	, acute and delayed
Symptoms/injuries after inhalation	May cause irritation to the respiratory tract. Overexposure to vapors may result in headache, nausea, drowsiness or dizziness.
Symptoms/injuries after skin contact	May cause skin irritation or burning sensation
Symptoms/injuries after eye contact	May cause eye irritation or injury
Symptoms/injuries after ingestion	May cause severe irritation or burns to the mucous membrane of the mouth, throat, esophagus and stomach

4.3 Indication of any immediate medical attention and special treatment needed

No additional information available

Section 5. **Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	Dry chemical, foam, carbon dioxide	
Unsuitable extinguishing media	Do not use heavy water stream	
5.2 Special hazards arising from the substance or mixture		
Reactivity	Thermal decomposition products may cause a health hazard.	
5.3 Advice for firefighters		
Firefighting instructions	Flammable Liquid! This material releases vapors when heated above ambient temperatures. Vapors can cause a flash fire. Use water spray or fog to cool exposed containers.	
Protective equipment for firefighters	Firefighters should always wear self-contained breathing apparatus (SCBA) and full protective gear when fighting any chemical fire.	
Other information	On heating or burning harmful gasses/vapors may be released. This product may cause the floor to become slippery.	

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

General measures	Extremely Flammable. Eliminate any ignition sources. Dike or impound spilled material. Use Non-sparking tools. All equipment must be grounded. Take proper precautions to ensure your own health and
	safety before attempting spill control or cleanup.
6.11 Protective Equipment	Equip cleanup crew with proper protective equipment.
6.2 Environmental precautions	Prevent entry to sewers and public waters.
	Notify authorities if liquid enters sewers or public waters.
6.3 Methods and materials for containment and cleaning up	
Methods for cleaning up	Soak up spills with inert solids, such as clay or diatomaceous earth.



NOX-CARB LIGHT BASE COMPONENT A Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Collect into vapor tight containers and dispose of properly.

Section 7. Handling and storage Precautions for safe handling Protective measures Wash hands and other exposed areas with soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use keep containers tightly closed. Avoid breathing vapor or mist. Hygiene measures Wash contaminated clothing before reuse. 7.2 Conditions for safe storage, including any incompatibilities Storage conditions Store in accordance with local regulations. Store in original container in a cool well-ventilated place away from heat, sparks and open flame. Keep containers tightly closed until ready for use. Incompatible materials Strong oxidizing agents Storage temperature Store in a cool dry environment away from sources of ignition.

Section 8. Exposure controls/personal protection

8.1 Control parameters Occupational exposure limits

Ingredient name	Occupational exposure limits ACGIH TLV (United States)	
Xylene	TWA: 100 ppm 8 hours	
Cumene	TWA: 50 ppm 8 hours	
1,2,4- Trimethylbenzene	TWA: 25 ppm 8 hours	
Solvent Naphtha	TWA: 100 ppm 8 hours	
Appropriate engineering controls	Use with adequate ventilation to keep product vapor concentrations below specified TLV	
8.2 Exposure controls Appropriate engineering controls		
Eye and face protection	Chemical goggles and/or face shields are recommended to prevent potential eye contact, irritation or injury.	
Skin protection	Wear chemical resistant gloves and appropriate protective clothing and boots as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.	
Respiratory protection	General room ventilation is normally adequate. Avoid breathing the product mist or vapors. The use of an appropriate respirator is recommended whenever the airborne concentrations exceed the TLV.	

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties		
Appearance	Milky liquid	
Odor	Strong Aromatic Odor	
Odor Threshold	No data available	
PH	No data available	
Melting point	No data available	
Freezing point	No data available	
Boiling point	> 138 C (>280 F)	
Flash point	> 38 C > 100 F PMCC	
Relative evaporation rate (butyl acetate=1)	No data available	
Flammability (solid, gas) Flammable liquid and vapor		



NOX-CARB LIGHT BASE COMPONENT A Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

Upper/lower explosive limits Vapor pressure Vapor density Relative density (Specific gravity) Solubility Partition coefficient n-octanol/water Auto-ignition temperature Viscosity VOC content

No data available No data available No data available 1.21 Kg per Liter 10.1 Lbs per Gallon Water: Negligible No data available Not applicable No data available Less than 600 g/l

No additional information available

Extreme high or low temperatures.

Hazardous polymerization will not occur.

Stable under normal conditions

Strong acids and oxidizers

Section 10. Stability and reactivity

10.1 Reactivity

Carcinogenicity

10.2 Chemical stability

10.3 Possibility of hazardous reactions

10.4 Conditions to avoid

10.5 Incompatible materials

10.6 Hazardous decomposition products

Section 11. Toxicology information

11.1 Information on toxicological effects Acute toxicity Irritation/Corrosion Skin Eyes Respiration or skin sensitization Germ cell mutagenicity

No adverse effects expected under intended use. May cause skin irritation May causes serious eye irritation and damage. May cause respiratory irritation No data available

carbon monoxide, carbon dioxide, various hydrocarbon derivatives

Xylene3Cumene2B

2B - Limited evidence in humans and less than sufficient evidence in animals.

3 - Inadequate in humans and inadequate or limited in animals.

IARC

Reproductive toxicity

Specific target organ toxicity Single exposure Repeated exposure Aspiration hazard No data available

No data available No data available May be fatal if swallowed and enters airways

Section 12. Ecological information

12.1 Ecotoxicity	Not established
12.2 Persistence and degradability	Not established
12.3 Bio accumulative potential	Not established
12.4 Mobility in soil	No additional information available
12.5 Other adverse effects	Avoid release to the environment

SECTION 13. Disposal Considerations

13.1 Waste treatment methods

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment,



NOX-CARB LIGHT BASE COMPONENT A Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

storage and disposal for hazardous and nonhazardous wastes.

SECTION 14. Transport information In accordance with US DOT Not dangerous goods in sense of transport regulations. In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA 14.1 UN number UN1263 14.2 UN proper shipping name Paint Related Material 14.3 Transport hazard class(es) 3 14.4 Packing group Ш 14.5 Environmental hazards No additional information available 14.6 Special precautions for user 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No additional information available 14.8 Transport in bulk according to CFR 49 173.15 Not applicable SECTION 15. **Regulatory** information 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1.2 USA Regulations Section 313 Contains the following ingredients at or above the reporting level requirements of Section 313. This information must be included in all SDS's copied or distributed for this material. CHEMICAL CAS # MAX WEIGHT % **Xvlene** 1330-20-7 1.1 1,2,4- Trimethylbenzene 95-63-6 16.0 Cumene 98-82-8 0.6 TSCA All ingredients are listed or exempted **Proposition 65** WARNING NOT FOR SALE IN CALIFORNIA 15.1.3 Canada Regulations This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. DSL All ingredients are listed or exempted 15.2 Chemical safety assessment A Chemical Safety Assessment has not been carried out. Other information Section 16. Date of issue 7-17-2023 Version 3.0 Number 151 Date of previous issue 8-3-2021 Preparer Nox-Crete, Inc. **Reference Documentation**

The information and recommendations contained herein are, to the best of Nox-Crete, Inc.'s knowledge and belief, accurate and reliable as of the date issued. You can contact Nox-Crete, Inc. to ensure that this document is the most current available from Nox-Crete, Inc. The information and recommendations are offered for the buyer's/user's consideration and examination. It is the buyer's/user's responsibility to satisfy themselves that the product is suitable for the intended use. Appropriate warnings and safe-handling procedures should be provided to all handlers and users. Since



NOX-CARB LIGHT BASE COMPONENT A Sa

Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Since the information provided herein may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and buyer/user may rely thereon only at their risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further, since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and /or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each buyer/user repackages this product, it is the buyer's/user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Nox-Crete, Inc. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with this product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part is not permitted.

Full text of H and P phrases

Flam Liq. 3	H226
Asp. Tox. 1	H304
resp. irrit. STOT SE 3	H335
STOT SE 3 drowsiness	H336
Carc. 2	H351

H226 - Flammable liquid and vapor

Flam Liq. 3

- H304 May be fatal if swallowed and enters airways
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H351 Suspected of causing cancer

P201 - Obtain special instructions before use

- P210 Keep away from heat/sparks/open flames/hot surfaces-No smoking
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical/ventilating/light/equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P303+P361+P353 - IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower

- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312 Call a poison center/doctor if you feel unwell.

P331 - Do NOT induce vomiting

- P370+P378 In case of fire: Use Dry chemical, foam, carbon dioxide for extinction
- P403+P405+P235+P233 Store locked up in a cool well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.