nox-crete

## PERFECT EXTREME CONCRETE SPRAYER

FOR CONSISTENT APPLICATION OF LOW VOC SOLVENT-BASED BONDBREAKERS, CURE AND SEALERS AND DECORATIVE SEALERS

## FEATURES .....

- 3.4 gal. (12.9L) Tank with 2.75 gal (10.4L) fill capacity
- Heavy-duty stainless steel tank with an external hammered coating finish that resists corrosion and chemical degradation
- Built-In pressure gauge for monitoring tank pressure
- Maximum pressure of 116psi (8 bar / 800 kpa)
- Can be pressurized using hand pump or optional air compressor fill valve
- · Tank equipped with pressure relief valve to prevent overcharging
- Includes 5ft. (152cm) of chemical resistant hose that remains flexible even in below freezing conditions
- Utilizes a heavy-duty, pistol grip shut-off that is designed for comfort and long-term durability under extreme conditions
  - Incorporates a heavy-duty stainless steel wand made from pipe that won't bend like traditional spray wands made from brass or plastic tube



chemical solutions to concrete problems



## **FEATURES**

- Includes two backback-style carrying straps that helps free up the hands of the sprayer operator
- Includes a wide funnel-style opening to reduce spills during filling of sprayer
- Pump includes a funnel cover to prevent dirt and debris from collecting in the fill area where it can ultimately end up in the tank
- Wide base prevents sprayer from falling over and includes a convenient storage area for spray end of wand
- Includes a 50 mesh filter located immediately behind the spray tip
- Available with air compressor fill valve with pressure limiting check valve to prevent overcharging

## **OPTIONAL EQUIPMENT**

- Air compressor fill valve
- Extra spray tips in various sizes



For more information, review the sprayer manual. Sprayer parts available from Nox-Crete.