## PERFECT PRECAST SPRAYER

2.75 2.5 ox-crete

COMMERCIAL-GRADE SPRAYER SPECIFICALLY DESIGNED FOR LIGHT, CONSISTENT APPLICATION OF CONCRETE FORM RELEASE AGENTS FOR THE PRECAST INDUSTRY

## FEATURES .....

- 3.4 gal. (12.9L) Tank with 2.75 gal (10.4L) fill capacity
- Heavy-duty stainless steel tank with an external hammered coating finish that resists corrosion and chemical degradation
- · Built-In pressure gauge for monitoring tank pressure
- Maximum pressure of 116psi (8 bar / 800 kpa)
- Can be pressurized using hand pump or air compressor fill valve
- Tank equipped with pressure relief valve to prevent overcharging
- Includes 5ft. (152cm) of chemical resistant hose that remains flexible even in below freezing conditions
- Utilizes a heavy-duty, pistol grip shut-off that is designed for comfort and long-term durability under extreme conditions
  - Incorporates a heavy-duty stainless steel wand made from pipe that won't bend like traditional spray wands made from brass or plastic tube

nox-cret<sup>®</sup>e

chemical solutions to concrete problems







## **FEATURES**

- Includes two backback-style carrying straps that helps free up the hands of the sprayer operator
- Includes a wide funnel-style opening to reduce spills during filling of sprayer
- Pump includes a funnel cover to prevent dirt and debris from collecting in the fill area where it can ultimately end up in the tank
- Wide base prevents sprayer from falling over and includes a convenient storage area for spray wand
- Includes a 100 mesh filter located immediately behind the spray tip
- Includes 40psi pressure-regulating non-dripping control flow valve

## **OPTIONAL EQUIPMENT**

Extra spray tips in various sizes



For more information, review the sprayer manual. Sprayer parts available from Nox-Crete.