



chemical solutions to concrete problems

# SILCOSEAL CLASSIC FAST DRY

## Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

### Section 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product Form	Mixture
Trade Name	SILCOSEAL CLASSIC FAST DRY
Product Code	SSCFD

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use	Industrial. For professional use only.
-----	--

#### 1.2.2 Uses Advised Against

No additional information available

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer

NOX-CRETE, INC.  
1444 SOUTH 20<sup>TH</sup> STREET  
OMAHA, NE 68108  
Tel: 402-341-2080  
Fax: 402-341-9752  
E-Mail: [corporate@nox-crete.com](mailto:corporate@nox-crete.com)  
Web Site: [www.nox-crete.com](http://www.nox-crete.com)

#### 1.4 Emergency telephone number

Emergency Number	Chemtrec (800) 424-9300 Chemtrec Outside of U.S. 703-527-3887
------------------	--

### Section 2. Hazards identification

#### 2.1 Classification of the substance or mixture

Flam. Liq. 3	H226
Asp. Tox. 1	H304
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H335
STOT SE 3	H336
Carc. 2	H351
Repr. 2	H361
STOT RE 2	H373

Full text of H and P phrases see section 16

Adverse physiochemical, human health and environmental effects

No additional information available

#### 2.2 Label elements

Hazard pictograms



Signal word

**Danger**



chemical solutions to concrete problems

# SILCOSEAL CLASSIC FAST DRY

## Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

### Hazard statements

H226: Flammable liquid and vapor  
H304: May be fatal if swallowed and enters airways  
H315: Causes skin irritation  
H318: Causes serious eye damage  
H335: May cause respiratory irritation  
H336: May cause drowsiness or dizziness  
H351: Suspected of causing cancer  
H361: Suspected of damaging fertility or the unborn child  
H373: May cause damage to organs

### Precautionary statements

#### Prevention:

P201: Obtain special instructions before use.  
P202: Do not handle until all safety precautions have been read and understood.  
P210: Keep away from heat/sparks/open flames/hot surfaces-No smoking.  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical/ventilating/light/equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264: Wash exposed area's thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.

#### Response:

P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P303+P361+P353: IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+P310: IF IN EYES: Immediately call a POISON CENTER or doctor/physician.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.  
P308+P313 - IF exposed or concerned - Get medical advice/attention  
P331: Do NOT induce vomiting.

#### Storage:

P403+P235+P233: Store in a cool well-ventilated place. Keep container tightly closed.

#### Disposal:

P405: Store locked up.  
P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

### 2.3 Other hazards

None known

Full text of H and P phrases: see section 16

## Section 3. Composition / information on ingredients

### 3.1 Substances



chemical solutions to concrete problems

# SILCOSEAL CLASSIC FAST DRY

## Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

Not applicable

### 3.2 Mixture

Name	Product identifier	%
Toluene	108-88-3	<10.0
Organic solvent	Trade Secret	Trade Secret
Alcohol	Trade Secret	Trade Secret
Ethylbenzene	100-41-4	<0.05-0.25
Xylene	1330-20-7	< 40-65

Pursuant to 29CFR 1910.1200(i) the specific chemical identity (and / or) concentration may be withheld as Trade Secret, while all health and safety properties and effects are included in the SDS. Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).

## Section 4. First aid measures

### 4.1 Description of first aid measures

#### First-aid measures general

Get medical advice/attention if you feel unwell. Never give anything by mouth to an unconscious person.

#### First-aid measures after inhalation

If the individual experiences nausea, dizziness, has difficulty in breathing seek a healthcare professional immediately. In all cases of doubt, or when symptoms persist, seek medical advice. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a Poison Center or doctor/physician.

#### First-aid measures after skin contact

If skin irritation persists, seek medical attention. Remove or take off immediately all contaminated clothing. Rinse skin with water or shower. Wash off immediately with soap and plenty of water.

#### First-aid measure after eye contact

When contact lenses are worn, remove if possible. In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes while holding eyelids apart. Get medical attention immediately.

#### First-aid measures after ingestion

Rinse mouth. DO NOT induce vomiting. Get medical attention immediately.

### 4.2 Most important symptoms and effects, acute and delayed

#### Symptoms/injuries after inhalation

May cause irritation to the respiratory tract. Overexposure to vapors may result in headache, nausea, drowsiness or dizziness.

#### Symptoms/injuries after skin contact

May cause skin irritation or burning sensation

#### Symptoms/injuries after eye contact

May cause eye irritation or injury

#### Symptoms/injuries after ingestion

May cause severe irritation or burns to the mucous membrane of the mouth, throat, esophagus and stomach.

### 4.3 Indication of any immediate medical attention and special treatment needed

No additional information available

## Section 5. Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Dry chemical, foam, carbon dioxide

#### Unsuitable extinguishing media

Do not use heavy water stream

### 5.2 Special hazards arising from the substance or mixture



chemical solutions to concrete problems

# SILCOSEAL CLASSIC FAST DRY

## Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

### Reactivity

#### 5.3 Advice for firefighters

#### Firefighting instructions

#### Protective equipment for firefighters

#### Other information

Thermal decomposition products may cause a health hazard.

This material releases vapors when heated above ambient temperatures. Vapors can cause a flash fire. Use water spray or fog to cool exposed containers.

Firefighters should always wear self-contained breathing apparatus (SCBA) and full protective gear when fighting any chemical fire.

On heating or burning harmful gasses/vapors may be released.

This product may cause the floor to become slippery.

## Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### General measures

Eliminate any ignition sources. Dike or impound spilled material. Take proper precautions to ensure your own health and safety before attempting spill control or cleanup.

#### 6.11 Protective Equipment

Equip cleanup crew with proper protective equipment.

#### 6.2 Environmental precautions

Prevent entry to sewers and public waters.

Notify authorities if liquid enters sewers or public waters.

### 6.3 Methods and materials for containment and cleaning up

#### Methods for cleaning up

Soak up spills with inert solids, such as clay or diatomaceous earth.

Collect into vapor tight containers and dispose of properly.

## Section 7. Handling and storage

### 7.1 Precautions for safe handling

#### Protective measures

Wash hands and other exposed areas with soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in work areas to prevent formation of vapor. When not in use keep containers tightly closed. Avoid breathing vapor or mist.

#### Hygiene measures

Wash contaminated clothing before reuse.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Store in accordance with local regulations. Store in original container in a cool well-ventilated place away from heat, sparks and open flame. Keep containers tightly closed until ready for use.

#### Incompatible materials

Strong oxidizing agents. Strong acids or bases and select amines.

#### Storage temperature

Store in a cool dry environment away from sources of ignition.

## Section 8. Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

Ingredient name	Occupational exposure limits ACGIH TLV (United States)
Toluene	TWA: 20 ppm 8 hours
Organic Solvent	TWA: 500 ppm 8 hours
Alcohol	TWA: 50 ppm 8 hours
Ethylbenzene	TWA: 20 ppm 8 hours



chemical solutions to concrete problems

# SILCOSEAL CLASSIC FAST DRY

## Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

Xylene	TWA: 100 ppm 8 hours
--------	----------------------

### 8.2 Exposure controls

#### Appropriate engineering controls

Use with adequate ventilation to keep product vapor concentrations below specified TLV

#### Eye and face protection

Chemical goggles and/or face shields are recommended to prevent potential eye contact, irritation or injury.

#### Skin protection

Wear chemical resistant gloves and appropriate protective clothing and boots as required to prevent skin contact. Wash exposed skin frequently with soap and water. Soiled clothing should be laundered before reuse.

#### Respiratory protection

General room ventilation is normally adequate. Avoid breathing the product mist or vapors. The use of an appropriate respirator is recommended whenever the airborne concentrations exceed the TLV.

## Section 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance	Red liquid
Odor	Mild Solvent Odor
Odor Threshold	No data available
PH	No data available
Melting point	No data available
Freezing point	No data available
Boiling point	94 C (200 F)
Flash point	23 C 73.4 F PMCC
Relative evaporation rate (butyl acetate=1)	No data available
Flammability (solid, gas)	Flammable liquid and vapor
Upper/lower explosive limits	No data available
Vapor pressure	No data available
Vapor density	No data available
Relative density (Specific gravity)	0.81 Kg per Liter 6.7 Lbs per Gallon
Solubility	Water: Insoluble
Partition coefficient n-octanol/water	No data available
Auto-ignition temperature	No data available
Viscosity	No data available
VOC content	726 g/l

## Section 10. Stability and reactivity

### 10.1 Reactivity

No additional information available

### 10.2 Chemical stability

Stable under normal conditions

### 10.3 Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4 Conditions to avoid

Extreme high or low temperatures.

### 10.5 Incompatible materials

Strong acids, bases, oxidizers and select amines.

### 10.6 Hazardous decomposition products

carbon monoxide, carbon dioxide, various hydrocarbon derivatives

## Section 11. Toxicology information

### 11.1 Information on toxicological effects

#### Acute toxicity

No adverse effects expected under intended use.



chemical solutions to concrete problems

# SILCOSEAL CLASSIC FAST DRY

## Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), Hazardous Products Regulation (HPR) (WHMIS 2015)

**Irritation/Corrosion**    **Skin**  
                                 **Eyes**  
**Respiration or skin sensitization**  
**Germ cell mutagenicity**

May cause skin irritation  
May causes serious eye irritation and damage.  
May cause respiratory irritation  
No data available

**Carcinogenicity**                      **IARC**

Xylene	3
Toluene	3
Ethylbenzene	2B

2B - Limited evidence in humans and less than sufficient evidence in animals.

3 - Inadequate in humans and inadequate or limited in animals.

**Reproductive toxicity**  
**Specific target organ toxicity**  
                    **Single exposure**  
                    **Repeated exposure**  
**Aspiration hazard**

No data available  
  
No data available  
No data available  
May be fatal if swallowed and enters airways

## Section 12. Ecological information

<b><u>12.1 Ecotoxicity</u></b>	No data available
<b><u>12.2 Persistence and degradability</u></b>	No data available
<b><u>12.3 Bioaccumulative potential</u></b>	No data available
<b><u>12.4 Mobility in soil</u></b>	No data available
<b><u>12.5 Other adverse effects</u></b>	Avoid release to the environment

## SECTION 13. Disposal Considerations

### **13.1 Waste treatment methods**

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all applicable local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

## SECTION 14. Transport information

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA

<b><u>14.1 UN number</u></b>	UN1263
<b><u>14.2 UN proper shipping name</u></b>	UN1263, Paint Related Material,3,PGIII
<b><u>14.3 Transport hazard class(es)</u></b>	Flammable Liquid
<b><u>14.4 Packing group</u></b>	PGIII
<b><u>14.5 Environmental hazards</u></b>	No additional information available
<b><u>14.6 Special precautions for user</u></b>	No additional information available
<b><u>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</u></b>	No additional information available
<b><u>14.8 Transport in bulk according to CFR 49 173.15</u></b>	Not applicable



chemical solutions to concrete problems

# SILCOSEAL CLASSIC FAST DRY

## Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

### SECTION 15. Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.2 USA Regulations

###### Section 313

Contains the following ingredients at or above the reporting level requirements of Section 313. This information must be included in all SDS's copied or distributed for this material.

###### CHEMICAL

Toluene

###### CAS #

108-88-3

###### MAX WEIGHT %

< 10.0

Xylene

1330-20-7

< 40.0-65.0

Ethylbenzene

100-41-4

< 0.05-0.25

###### TSCA

###### Proposition 65

All ingredients are listed or exempted

This product NOT FOR SALE in the State of California.

##### 15.1.3 Canada Regulations

This SDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR.

###### DSL

###### 15.2 Chemical safety assessment

All ingredients are listed or exempted

A Chemical Safety Assessment has not been carried out.

### Section 16. Other information

Date of issue / revision

3-5-2025

Version

1.0

Number

1061

Date of previous issue / revision

Preparer

Nox-Crete, Inc.

###### Reference Documentation

The information and recommendations contained herein are, to the best of Nox-Crete, Inc.'s knowledge and belief, accurate and reliable as of the date issued. You can contact Nox-Crete, Inc. to ensure that this document is the most current available from Nox-Crete, Inc. The information and recommendations are offered for the buyer's/user's consideration and examination. It is the buyer's/user's responsibility to satisfy themselves that the product is suitable for the intended use. Appropriate warnings and safe-handling procedures should be provided to all handlers and users. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Since the information provided herein may have been obtained in part from independent laboratories or other sources not under our direct supervision, no representation is made that the information is accurate, reliable, complete or representative and buyer/user may rely thereon only at their risk. We have made no effort to censor or to conceal deleterious aspects of this product. Further, since we cannot anticipate or control the many different conditions under which this information or our products may be used, we make no guarantee that the health and/or safety precautions we have suggested will be adequate for all individuals and/or situations involving its handling or use. Likewise, we make no guarantee or warranty of any kind that the use or disposal of this product is in compliance with all federal, state or local laws. It is the obligation of each buyer/user of the product mentioned herein to determine and comply with the requirements of all applicable statutes. If buyer/user repackages this product, it is the buyer's/user's responsibility to ensure proper health, safety and other necessary information is included with and/or on the container. Nox-Crete, Inc. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with





chemical solutions to concrete problems

## SILCOSEAL CLASSIC FAST DRY

### Safety Data Sheet

According to Regulation 29 CFR 1910.1200, Regulation (EC) No. 1272/2008 (CLP)(GHS), *Hazardous Products Regulation* (HPR) (WHMIS 2015)

this product. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part is not permitted.

#### Full text of H and P phrases

Flam. Liq. 3	H226: Flammable liquid and vapor
Asp. Tox. 1	H304: May be fatal if swallowed and enters airways
Skin Irrit. 2	H315: Causes skin irritation
Eye Dam. 1	H318: Causes serious eye damage
STOT SE 3	H335: May cause respiratory irritation
STOT SE 3	H336: May cause drowsiness or dizziness
Carc. 2	H351: Suspected of causing cancer
Repr. 2	H361: Suspected of damaging fertility or the unborn child
STOT RE 2	H373: May cause damage to organs

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat/sparks/open flames/hot surfaces-No smoking.

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical/ventilating/light/equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P264: Wash exposed area's thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P310: IF IN EYES: Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.

P308+P313 - IF exposed or concerned - Get medical advice/attention

P331: Do NOT induce vomiting.

P403+P235+P233: Store in a cool well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.